

MATTEX (-15) READY TO USE RED ANTIFREEZE

Product Description and Field of Use:

It is a monoethylene glycol based ready-to-use antifreeze formulated with superior anti-corrosion, anti-wear and anti-foam additives to be used in the coolant of gasoline and diesel engines. It is recommended for use in cold regions down to -15°C. It is suitable for use in gasoline and diesel engines. It is ready for direct use. Not recommended for use in regions colder than -15°C.

Properties and Benefits

- Thanks to special anti-corrosion additives, it protects the copper and brass materials in the engine against corrosion and does not damage the gaskets.
- It prevents cracking and other damage caused by expansion in cold climates.
- Compatible with all sealing components.
- Does not contain nitrite, boron, phosphorus, silicate, amine
- Ready for direct use

SPECIFICATIONS/ APPROVALS

-

TECHNICAL SPECIFICATIONS*

<u>Teknik Spekler</u>	<u>Metod</u>	<u>TİPİK DEĞERLER</u>
Apperance	-	Clear
Color	ASTM D 1122	Red
Boiling Point C	ASTM D 1120	115
PH Value	ASTM D 1287	7-11
Freezing Point C	ASTM D 1177	-15

* Typical values may vary slightly from production to production.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet