

## MATTEX ATF DEXRON III

### Product Description and Field of Use:

It is a high-performance synthetic automatic transmission fluid produced by blending high-quality synthetic base oils and special additives. It has been developed especially for use in automatic transmissions of passenger and heavy-duty vehicles, but is also suitable for use in hydraulic steering applications.

### Properties and Benefits

- Offers excellent lubrication performance with excellent viscosity even at very low operating temperatures.
- Long service life provided by high thermal and oxidation stability helps to reduce operational costs by extending oil change intervals.
- Thanks to its superior anti-wear feature, it protects the transmission components against wear and extends the life of the transmission.
- Excellent lubrication and friction performance ensures smooth gear changes, ensuring excellent driving pleasure

### SPECIFICATIONS/ APPROVALS

ALLISON C-4 /FORD MERCON V /GM DEXRON III-H/ MAN 339 Type V2 /MAN 339 Type Z2/ MB 236.9 /VOITH H55.6336.XX  
Volvo 97341 /ZF TE-ML 04D, 05L, 14B, 16L, 20B, 21L, 25B

### TECHNICAL SPECIFICATIONS\*

<u>TEST</u>	<u>BİRİM</u>	<u>TEST METODU</u>	<u>TİPİK DEĞERLER</u>
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.85
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	6.4-8.9
Viscosity Index	-	ASTM D 2270	145
Flash Point (°C)	°C	ASTM D 92	195
Pour Point (°C)	°C	ASTM D 97	-45

\* Typical values may vary slightly from production to production.

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet