

## MATTEX BRAKE FLUID DOT-4

### Product Description and Field of Use:

It is a synthetic high performance hydraulic brake fluid based on polyethylene glycol, polyethylene glycol ether and special additive technology. It meets all the requirements of brake fluid, even at high temperatures caused by friction.

### Properties and Benefits

- Hydraulic Brake Fluid is a special synthetic based fluid and is used for motor vehicle hydraulic brake weight and usage.
- It meets minimum ERBP and WERBP requirements, therefore minimizing the risk of vapor lock under severe conditions.
- While the product keeps the system running in very cold weather, it prevents leakage at high operating temperatures and maintains the fluidity in the system.
- It protects all different metal parts in the brake system against corrosion and prevents the system from malfunctioning

### SPECIFICATIONS/ APPROVALS

SAE J 1703 , SAE J 1704 , FMVSS 116 DOT 4 , ISO 4925 Class 4 , MAN

### TECHNICAL SPECIFICATIONS\*

<u>TEST</u>	<u>BİRİM</u>	<u>TEST METODU</u>	<u>TİPİK DEĞERLER</u>
K. Viscosity, @ 40°C	cSt	ASTM D 445	1210-1570 mm <sup>2</sup> /s
K. Viscosity, @ 100°C	cSt	ASTM D 445	2-2,2mm <sup>2</sup> /s
Flashing Point	°C	ASTM D 92	255

\* Typical values may vary slightly from production to production.

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet