

MATTEX IMPULSE 0W-20 SP

Product Description and Field of Use:

It is a superior performance, fully synthetic engine oil developed to provide fuel economy and long life for the new generation Volkswagen group (VW, Porsche, Audi, Skoda, Seat) vehicles, which requires VW 508.00 / 509.00 specifications, and all modern technology vehicle engines with direct injection, turbocharged and multi-valve.

Properties and Benefits

- Helps to control sludge accumulation and deposits.
- It ensures clean engines and longer component life.
- It helps to reduce oil consumption and wear.
- It offers a durable oil film that provides complete lubrication in all traffic conditions and temperatures.
- Even at the lowest temperatures, it minimizes wear with excellent flow performance during engine start-up.
- It provides superior protection for the new generation of VW group engines with high volumes and low tolerances.

SPECIFICATIONS/ APPROVALS

API SP/ SN Plus API ACEA C5-16, VW 508 00/509 00, VW TL 52577, Porsche C20

TECHNICAL SPECIFICATIONS*

TEST	BİRİM	TEST METODU	TİPİK DEĞERLER
Density, @15 °C	g/cm ³	ASTM 4052	0.831
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	5.6-9.3
Viscosity Index	-	ASTM D 2270	168
Flash Point (°C)	°C	ASTM D 92	220
Pour Point (°C)	°C	ASTM D 97	-40

* Typical values may vary slightly from production to production.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet