

## MATTEX IMPULSE 0W-30 SN/CF

### PRODUCT DESCRIPTION AND USAGE AREA

It is a superior performance fully synthetic engine oil produced with specially selected synthetic base oils and additive technology, suitable for use in gasoline, passenger diesel and light commercial vehicles.

### PROPERTIES

- Even at the lowest temperatures, it minimizes wear with excellent flow performance during engine start-up.
- It reduces friction even at low temperatures, improving engine performance and ensuring fuel economy thanks to its superior technology.
- It protects the engine against corrosion, and provides excellent resistance against wear.
- It creates a durable oil film in the engine at all temperatures, thus minimizing engine wear thanks to its high-viscosity index.
- It provides excellent engine protection against sediment and soot formation thanks to its superior cleaning power

### SPECIFICATIONS/ APPROVALS

API SN/ SL/CF, ACEA A3/B4, BMW LL-98; GM LL-B-025; MB 229.3; Renault RN0700, RN0710; VW 502.00/505.00

### TECHNICAL SPECIFICATIONS \*

TEST	BİRİM	TEST METODU	TİPİK DEĞERLER
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.846
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	9.3-12.5
Viscosity Index	-	ASTM D 2270	160
Flash Point (°C)	°C	ASTM D 92	205
Pour Point (°C)	°C	ASTM D 97	-40

\* Typical values may vary slightly from production to production.

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet