

## MATTEX IMPULSE 10W-40 SN/CF

### PRODUCT DESCRIPTION AND USAGE AREA

It is a synthetic engine oil produced to meet the lubrication needs of normal suction and turbocharged engines as a result of blending high-quality base oils and high-tech additives. It is an engine oil developed to meet the lubrication requirements of gasoline, light diesel and LPG vehicles.

### PROPERTIES

- Helps extend engine life by protecting against wear even in everyday driving conditions.
- Provides constant lubrication in all climates and road conditions.
- Can be used in gasoline, diesel and LPG compatible engines.
- Provides faster initial start-up and very fast protection.  
Saves maximum fuel and keeps the engine clean

### SPECIFICATIONS/ APPROVALS

API SN/CF; ACEA A3/B4; MB 229,1; MB 229,3; RN0700/0710; PSA B71 2300; VW 501.00/505.00

### TECHNICAL SPECIFICATIONS \*

<u>TEST</u>	<u>BİRİM</u>	<u>TEST METODU</u>	<u>TİPİK DEĞERLER</u>
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.87
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	12.5-16.3
Viscosity Index	-	ASTM D 2270	160
Flash Point (°C)	°C	ASTM D 92	220
Pour Point (°C)	°C	ASTM D 97	-36

\* Typical values may vary slightly from production to production.

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet