

## MATTEX IMPULSE C3 5W-30 SN/CF

### Product Description and Field of Use:

It is a fully synthetic engine oil that is compatible with the exhaust emission systems of gasoline, passenger diesel and light commercial vehicles that meet the requirements of Euro 4 and 5 emission standards, especially with diesel particulate filter (DPF).

### Properties and Benefits

- Provides unique protection against wear and corrosion thanks to its high-tech synthetic base oils and high-performance additives
- It reduces friction under all temperatures, improving engine performance and ensuring fuel economy thanks to its superior technology.
- Provides excellent protection against engine corrosion and wear.
- It creates a durable oil film in the engine at all temperatures, thus minimizing engine wear thanks to its high-viscosity index.
- With the help of detergent-dispersant additives in its content, it distributes the particles formed as a result of combustion in the environment, prevents the accumulation of deposits and increases the performance of the engine.

### SPECIFICATIONS/ APPROVALS

API SN/CF, ACEA C3, MB 229.51, 229.31; BMW LL-04; GM dexos2 TM; Chrysler MS-11106, VW504 00/507 00, Porsche C30/C40

### TECHNICAL SPECIFICATIONS\*

<u>TEST</u>	<u>BİRİM</u>	<u>TEST METODU</u>	<u>TİPİK DEĞERLER</u>
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.851
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	9.3-12.5
Viscosity Index	-	ASTM D 2270	165
Flash Point (°C)	°C	ASTM D 92	210
Pour Point (°C)	°C	ASTM D 97	-40

\* Typical values may vary slightly from production to production.

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet