

MATTEX IMPULSE C4 LA 5W-30 SN/CF

PRODUCT DESCRIPTION AND USAGE AREA

It is a high-performance synthetic engine oil developed for gasoline and DPF-equipped diesel engines of Mercedes, Renault and Nissan vehicles. It can be safely used in diesel engines which require oil use at Renault RN 0720 approved and ACEA C4 performance level.

PROPERTIES

- Ensures maximum environmental protection by contributing to low exhaust emission levels
- Ensures a long life of the diesel particulate filter thanks to its low SAPS content.
- Since it has been produced with Low Friction Technology and thanks to its excellent fluidity performance, it creates a durable oil film at every temperature, minimizing the wear that occurs during engine start-up and warm-up.
- Provides easy start-up and fuel economy in cold weather.
- Distributes the dirt formed as a result of burning in the environment and prevents the accumulation of sediment thanks to the detergent-dispersant additives it contains

SPECIFICATIONS/ APPROVALS

API SN; ACEA C4; Renault RN 0700; RN 0720 MB APPROVAL 226.51; MB 229.51

TECHNICAL SPECIFICATIONS *

TEST	BİRİM	TEST METODU	TİPİK DEĞERLER
Density, @15 °C	g/cm ³	ASTM 4052	0.849
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	9.3-12.5
Viscosity Index	-	ASTM D 2270	170
Flash Point (°C)	°C	ASTM D 92	210
Pour Point (°C)	°C	ASTM D 97	-39

* Typical values may vary slightly from production to production.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet