

MATTEX SMART 4T 10W-40 MA

PRODUCT DESCRIPTION AND USAGE AREA

Is a high quality synthetic motorcycle oil crafted with advanced technology additives . It can be used safely in four seasons on air or water cooled motorcycles with four strokes and high performance . It is also suitable for Japanese and European motorcycles where API SL and /or JASO MA / MA2 specifications are recommended .

PROPERTIES

- Provides long life for engines and their parts thanks to its high resistance against abrasion, rust and corrosion.
- Provides silent and comfortable gear shifting by balancing the friction at clutch system even under high engine temperatures thanks to its formula being product of advanced technology.
- Provides maximum protection against abrasion which may occur during the first operation thanks to its easy fluidity capacity even at very low temperatures.
- Helps the engine to operate cleanly and smoothly by keeping formation of residue under control at high temperatures.

SPECIFICATIONS/ APPROVALS

API SL , JASO MA2 (T9 03 :2011),JASO MA (T903 :2011),JASO MB (T9 03:2011)

TECHNICAL SPECIFICATIONS*

<u>TEST</u>	<u>BİRİM</u>	<u>TEST METODU</u>	<u>TİPİK DEĞERLER</u>
Density, @15 °C	g/cm ³	ASTM 4052	0,865
Kinematic Viscosity (100°C, cSt)	cSt	ASTM D 445	12,5-16,3
Viscosity Index	-	ASTM D 2270	150
Flash Point (°C)	°C	ASTM D 92	220
Pour Point (°C)	°C	ASTM D 97	-36

* Typical values may vary slightly from production to production.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water.Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet